

Vlucht in (m)	Hijslasten in (t) vlg. DIN 15019, Bl. 2, op de hoofdgiek																Vlucht in (m)	
	Contragewicht 29,4 t																	
	Afgestempeld 360°																	
Uithouders volledig uitgeschoven 8,00 m																		
Hoofdgiek lengte (m)																		
	12,20		21,00		21,00		29,85		29,85		38,70		38,70		47,50			
	∠	1)	∠		∠		∠		∠		∠		∠		∠			
3,0	69	120,0*	112,0	78	50,0	78	21,0										3,0	
3,5	67	110,0	103,0	77	50,0	77	21,0										3,5	
4,0	64	95,0	90,0	76	50,0	76	21,0	81	34,0	81	21,0						4,0	
4,5	61	81,0		74	50,0	74	21,0	80	34,0	80	21,0						4,5	
5,0	58	73,5		73	50,0	73	21,0	79	34,0	79	21,0						5,0	
6,0	52	62,5		70	50,0	70	21,0	77	34,0	77	21,0	81	21,0	81	21,0		6,0	
7,0	46	54,0		67	50,0	67	21,0	75	34,0	75	21,0	79	21,0	79	21,0	82	13,0	7,0
8,0	38	47,0		64	45,5	64	21,0	73	33,0	73	21,0	78	21,0	78	21,0	81	13,0	8,0
9,0	28	42,0		61	40,8	61	21,0	71	29,8	71	21,0	76	21,0	76	21,0	80	13,0	9,0
10,0				58	40,0	58	21,0	69	27,1	69	21,0	75	21,0	75	20,5	79	13,0	10,0
11,0				54	35,0	54	21,0	67	24,8	67	21,0	73	21,0	73	18,9	78	13,0	11,0
12,0				50	30,0	50	21,0	65	22,8	65	21,0	71	19,7	71	17,5	76	13,0	12,0
14,0				43	23,5	43	21,0	60	19,5	60	20,8	68	16,8	68	15,2	74	13,0	14,0
16,0				33	18,7	33	20,2	56	16,9	56	18,4	65	14,7	65	13,4	71	13,0	16,0
18,0				19	15,2	19	16,7	51	14,9	51	16,5	62	12,9	62	11,9	69	11,6	18,0
20,0								45	12,3	45	14,3	58	11,3	58	10,7	66	10,3	20,0
22,0								39	10,2	39	12,1	54	10,2	54	9,7	63	9,3	22,0
24,0								32	8,5	32	10,4	50	9,1	50	8,8	60	8,5	24,0
26,0								22	7,1	22	9,0	46	8,2	46	8,1	57	7,6	26,0
28,0												42	7,2	42	7,4	54	6,9	28,0
30,0												37	6,2	37	6,8	51	6,3	30,0
32,0												31	5,3	31	6,0	48	5,7	32,0
34,0												24	4,6	24	5,3	44	5,2	34,0
36,0												13	3,9	13	4,6	40	4,6	36,0
38,0																36	4,1	38,0
40,0																31	3,5	40,0
42,0																26	3,0	42,0
44,0																18	2,6	44,0
Teleskopeertoestand %																		
Tel. 1	0	50	25	100	50	100	75	100	Tel. 1									
Tel. 2	0	50	25	100	50	100	75	100	Tel. 2									
Tel. 3	0	0	25	0	50	50	75	100	Tel. 3									
Tel. 4	0	0	25	0	50	50	75	100	Tel. 4									
Code	17/18	17	18	17	18	17	18	17/18	Code									

1) Naar achteren met zwenkpal ingeschakeld.

* Hulpvoorziening noodzakelijk.

26.10.1995

De machinist dient op de hoogte te zijn met het instructieboek.

99707744422