



Sallitut taakat ATF 60-4

Sarjanro: 50572

Pääpuomistolle sallitut taakat (t) prEN 13000, mukaisesti

Vastapaino 13,2t

Tuettuna, nostoalue 360°

Tuentalveys 6,87 m

Nosto- säde (m)	Puomiston pituus (m)																Nosto- säde (m)																
	10,4	14,1	17,8	17,8	17,8	17,8	25,3	25,3	25,3	32,7	32,7	36,5	40,2																				
2,5	67	60,0*	71	30,0	75	20,0	75	30,0	75	13,0	77	13,0	77	17,0	77	11,8	80	13,0	80	9,5	78	13,0	78	9,2	78	9,0	80	7,0	80	7,0	7,0	2,5	
3,0	64	50,0	69	30,0	73	20,0	73	29,0	73	13,0	75	13,0	75	17,0	75	11,8	78	13,0	78	9,2	76	13,0	76	8,8	76	8,8	76	8,8	76	8,8	76	8,8	3,0
3,5	60	44,8	67	30,0	71	20,0	71	27,5	71	13,0	73	13,0	73	15,8	72	11,8	76	13,0	76	8,8	74	13,0	74	8,5	74	8,5	74	8,5	74	8,5	74	8,5	3,5
4,0	57	41,0	64	30,0	69	20,0	69	26,2	69	13,0	71	13,0	71	14,5	70	11,8	74	12,0	74	8,5	72	11,0	72	8,1	72	8,1	72	8,1	72	8,1	72	8,1	4,0
4,5	54	37,0	64	30,0	67	20,0	67	25,0	67	13,0	69	13,0	69	13,0	67	11,4	72	11,0	72	8,1	70	10,1	70	7,7	70	7,7	70	7,7	70	7,7	70	7,7	4,5
5,0	50	34,3	62	30,0	66	20,0	66	22,6	66	13,0	66	13,0	66	13,0	65	11,0	70	10,1	70	7,7	68	9,2	68	7,4	68	7,4	68	7,4	68	7,4	68	7,4	5,0
6,0	41	29,8	57	29,3	66	20,0	66	20,0	66	13,0	62	13,0	62	13,0	62	10,5	68	9,2	68	7,4	65	6,7	65	6,7	65	6,7	65	6,7	65	6,7	65	6,7	6,0
7,0	31	25,3	52	24,9	62	20,0	62	19,8	62	13,0	58	13,0	58	13,0	58	10,1	65	7,8	65	6,7	64	6,5	64	6,5	64	6,5	64	6,5	64	6,5	64	6,5	7,0
8,0	12	16,9	46	21,4	58	20,0	58	17,5	58	13,0	54	13,0	54	13,0	54	8,8	62	7,8	62	6,7	60	6,7	60	6,7	60	6,7	60	6,7	60	6,7	60	6,7	8,0
9,0			40	18,1	54	18,4	54	15,6	54	13,0	50	13,0	50	13,0	50	8,8	59	7,8	59	7,7	56	5,8	56	5,8	56	5,8	56	5,8	56	5,8	56	5,8	9,0
10,0			33	15,2	50	15,5	50	14,1	50	13,0	48	13,0	48	13,0	48	7,7	55	6,7	55	6,7	51	4,8	51	4,8	51	4,8	51	4,8	51	4,8	51	4,8	10,0
11,0			23	12,9	45	13,2	45	12,5	45	13,0	45	13,0	45	12,6	45	6,8	51	4,8	51	4,8	46	3,9	46	4,0	46	4,0	46	4,0	46	4,0	46	4,0	11,0
12,0					40	11,4	40	10,8	40	12,6	39	12,1	39	12,1	39	4,9	46	3,9	46	3,9	41	3,2	41	3,6	41	3,6	41	3,6	41	3,6	41	3,6	12,0
14,0					28	8,8	28	8,2	28	9,9	20	4,3	20	3,1	20	2,7	41	3,2	41	3,2	35	2,6	35	3,2	35	3,2	35	3,2	35	3,2	35	3,2	14,0
16,0											48	7,8	48	6,6	48	7,7	35	2,6	35	2,6	27	2,1	27	2,9	27	2,9	27	2,9	27	2,9	27	2,9	16,0
18,0											40	6,3	40	5,1	40	6,8	27	2,1	27	2,1	21	1,6	21	2,7	21	2,7	21	2,7	21	2,7	21	2,7	18,0
20,0											32	5,2	32	4,0	32	5,8	14	1,6	14	1,6	14	1,6	14	2,7	14	2,7	14	2,7	14	2,7	14	2,7	20,0
22,0											20	4,3	20	3,1	20	4,9	14	1,6	14	1,6	14	1,6	14	2,7	14	2,7	14	2,7	14	2,7	14	2,7	22,0
24,0																																	24,0
26,0																																	26,0
28,0																																	28,0
30,0																																	30,0
32,0																																	32,0
34,0																																	34,0
36,0																																	36,0
Teleskoopista käytössä %																																	
Tel. 1	0	50	50	100	0	50	100	0	50	100	0	50	100	0	50	100	0	50	100	0	50	100	0	50	100	0	50	100	0	50	100	Tel. 1	
Tel. 2	0	0	50	0	33	50	100	67	100	100	67	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	Tel. 2	
Tel. 3	0	0	0	0	33	50	0	67	50	100	67	50	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	Tel. 3	
Tel. 4	0	0	0	0	33	50	0	67	50	100	67	50	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	Tel. 4	
Koodi	010/110/210	010	110	010	210	110	010	210	010	210	010	210	010	210	010	210	010	210	010	210	010	210	010	210	010	210	010	210	010	210	Koodi		

* Asetettu taakse ylävaunun lukituksen suunnaisena. Lisänostovarustuksella, koodi 015

05.12.2000

Huomioi käyttöohje !

99707761734